

# CHEMFAB® OPEN MESH BELTING

## CHEMFAB® Open Mesh Belting

CHEMFAB Open Mesh Belting products are woven fiberglass belting materials designed for use in forced hot air curing ovens. CHEMFAB Open Mesh Belting products are designed to provide optimum performance in most drying applications.

## Typical Properties

Product Number	1580	1589	1590	3790
Standard Width (in.)	118	110	175	140
Weight Nominal (oz./yd. <sup>2</sup> )	14.7	13.5	13.0	14.0
Thickness Nominal (in.)	0.022	0.030	0.033	0.043
Breaking Strength, Warp (lbs./in.)	350	300	180	250
Breaking Strength, Fill (lbs./in.)	250	250	200	300
Porosity (SCFM/Ft. <sup>2</sup> )	270	750	1700	2000
Elongation at 40 lbs./in.	1% Max	1% Max	1% Max	1% Max
Weave Style	Mock Leno	Plain	Leno	Leno

The data listed above is for reference only. It is not intended for use as a guarantee of product performance.

**Dimensional Stability**—Width rigidity as well as length stability is maintained by CHEMFAB Open Mesh Belting in continuous use at temperatures up to 500°F. Under normal operating tensions (3 to 5 pounds per inch of width), CHEMFAB Open Mesh Belting holds its elongation and shrinkage to less than 1%.

**Release Properties**—The release properties of CHEMFAB Open Mesh Belting equal or exceed those of any other available belting material. The PTFE coating makes CHEMFAB Open Mesh Belting unique in its low coefficient of friction.

**Chemically Resistant**—The PTFE coating encapsulates the belting carcass and enhances its useful service life.

**Dynamic Strength**—CHEMFAB Open Mesh Belting's durability, coupled with low overall belt weight, allows optimal production speed with decreased power requirements.

**Temperature Resistant**—CHEMFAB Open Mesh Belting can be operated continuously at temperatures up to 500°F and will still maintain 100% of its operational profile.

**Fabrication Technology**—Saint-Gobain Performance Plastics belt seams have been specifically engineered to reduce the flex fatigue failure. Substantially reduced flex fatigue means longer belt life.

Saint-Gobain Performance Plastics offers a wide variety of seams specifically designed to reduce flex fatigue, including spiral, pin, metal and a truly endless belt. Special edge reinforcements with the same properties as the belt provides durable non-fraying edge to facilitate tracking.

UV Resistant and higher PTFE content versions are available for select CHEMFAB Open Mesh belting products.

**Saint-Gobain Performance Plastics Corporation**  
150 Gaylord Street  
Elk Grove Village, IL 60007  
**Customer Service: (800) 323-6677**  
Tel: (847) 364-0384  
Fax: (888) 394-1156

[www.fff.saint-gobain.com](http://www.fff.saint-gobain.com)

**Limited Warranty:** For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

**NOTE:** Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

CHEMFAB® is a registered trademark.  
©2004 Saint-Gobain Performance Plastics Corporation  
AFF-1049-PDF-0104-SGCS